

2" - 4" COMBO PULLER / CUTTERS

Accurate and Reliable Combination Puller / Cutters Offer a Variety of Options

- IDEAL FOR FLEXIBLE TUBING AND PROFILES.
- SERVO DRIVEN CUTTER FOR REDUCED MAINTENANCE AND INCREASED PRODUCTIVITY.
- USER-FRIENDLY TOUCHSCREEN CONTROL (IC MODELS).
- QUICK BLADE CHANGE REQUIRES NO TOOLS AND TAKES ONLY SECONDS (STANDARD ON INTELLICUT®, OPTIONAL ON SMARTCUT®).
- DURABLE, QUICK BUSHING CHANGE (STANDARD ON INTELLICUT®, OPTIONAL ON SMARTCUT®).
- SIDE-TO-SIDE CUTTER MOVEMENT FACILITATES STRING-UP AND COILING.
- OPTIONAL FRONT-TO-BACK MOVEMENT INCREASES BELT LIFE.
- HIGH TORQUE OPTION PROVIDES INCREASED FORCE AND CLEAN CUTS ON HEAVY WALL TUBING.



Model
IC-3 / 226-3



Increased Productivity Starts Here

SPECIFICATIONS

IntelliCut® (IC) Series and SmartCut® (SC) Series

MODEL	IC-2/218-3	IC-3/218-3	IC-4/218-4	IC-2/226-3	IC-3/226-3	IC-4/226-4
	SC-2/218-3	SC-3/218-3	SC-4/218-4	SC-2/226-3	SC-3/226-3	SC-4/226-4
Cut Capacity	2"	3"	4"	2"	3"	4"
Max. Cuts per Blade per Minute	IntelliCut® = 1,000 SmartCut® = 250					
Blade RPM Speed	IntelliCut® = 200 - 1,000 SmartCut® = 1,000					
Belt Contact Length	18"			26"		
Belt Width	3"		4"	3"		4"
Bushing Diameter	2-1/4"	3-1/4"	4-1/4"	2-1/4"	3-1/4"	4-1/4"
Power Supply	208-230/3/60 (Optional: 460/3/60)					

A wide variety of options are available.

Specifications subject to change without notice.

Electronic Caming Ensures the Best Cut-Length Tolerances in the Industry

Complete Cutter Mobility

All RDN puller/cutters feature standard side-to-side movement of the cutter, which facilitates easy string-up. The optional front-to-back adjustments dramatically increase belt life and allow the cutter to be moved out of the way for coiling.

Quick Bushing Change (standard on IntelliCut®, optional on SmartCut®)

Changing a bushing is as simple as turning a faucet; no tools are required. We've also eliminated wear factor by inserting a 1/2" solid steel plate around the steel threaded rods.

Quick Blade Change (standard on IntelliCut®, optional on SmartCut®)

No tools are needed. Just move the plate down, set a new blade in the holder and slide the plate back into place.



160 Covington Drive
Bloomington, IL 60108
PHONE: 630-893-4500
FAX: 630-893-5010
www.rdnmfg.com